

# **Stinson**°

ENVIRONMENTAL

**IMPACT** 

## **Performance Summary**

- Enhanced soil + stain resistance
- Enhanced abrasion resistance
- Fluid barrier
- Bleach-solution cleanable
- Enhanced fade resistance

#### **Environmental**

- GREENGUARD Certified
- REACH Compliant
- RoHS Compliant
- No fluorocarbons or perfluorinated compounds
- No added flame retardants
- No added antimicrobials
- Does not contain formaldehyde
- Formulated without Phthalates

## **Cleaning and Maintenance**

Cleaning Code: **(W-S)** For water-based stains use water-based cleaners. For oil-based stains use solvent-based cleaners. We recommend using a professional cleaning service.

Bleach solutions of up to 10% may be used for more difficult stains.

Dye lots may vary slightly.

- \* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.
- \*\* Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

Specifications	
Content	Vinyl Surface with Polyester Backing
Finish	Advanced Soil and Stain Resistant Top Coat
Backing	Polyester
Weight	32.0 oz./lin. yd.
Width	54 inches
Roll Size	30 yards
Performance Characteristics	
Abrasion Resistance** ASTM D-4157	Exceeds 500,000 double rubs - heavy duty
Break Strength ASTM D-751-06	Warp: 131.0 lbs. min., Fill: 95.0 lbs. min.
Tear Strength ASTM D-751-06	Warp: 8.5 lbs. min., Fill: 6.5 lbs. min.
Seam Slippage ASTM D-751-06	Warp: 60 lbs. min., Fill: 40 lbs. min.
Colorfastness to Light AATCC-16	650 Hours, Class 4.0
Crocking AATCC-8	Dry: Class 5.0, Wet: Class 5.0
Fluid Barrier	Inherent Fluid Barrier
Flammability*	
California Technical Bulletin 117-2013 Section 1	Passed
UFAC	Class 1
NFPA 260	Class 1
REDUCED	This product is formulated without phthalates.



# Stinson

C.F. Stinson, LLC 2849 Product Drive Rochester Hills, MI 48309

**P** 800 841 6279

F 248 299 3884