




QUICK EZ GLOSS COAT

F-JS-435



Cornhusker State Industries
800 Pioneers Blvd. • Lincoln, NE 68502
800-348-7537 • 402-471-4597
csi.salesandmarketing@nebraska.gov

Net 1 US Gallon (3.8 Liters)

- **EASY TO APPLY**
- **MAXIMUM BRILLIANCE**
- **ULTRA FAST RECOAT**
- **ALL ACRYLIC FORMULA**

Quick EZ Gloss Coat is an all acrylic, metal crosslinked, self-sealing floor finish developed especially to deliver optimal performance and excellent appearance in even heavy traffic areas.

Before applying Quick EZ Gloss Coat remove old sealer/finish using an appropriate stripper (F-JS-450 Quick EZ Stripper) following label directions. For use on vinyl composition, rubber, asphalt, quarry, terrazzo and sealed wood floors.

DIRECTIONS INITIAL APPLICATION

1. **REMOVE** old sealer/finish using an appropriate stripper and following label directions.
2. **APPLY** a thin coat of Quick EZ Gloss Coat using a clean finish mop.
3. **DRY:** Allow 20-30 minutes drying time.
4. **Apply** 3-4 coats for best results. Allow adequate drying time between each coat.

MAINTENANCE

1. **DUST MOP** the floor. Remove gum, labels, and other attached soil deposits with a long handled scraper or putty knife.
2. **DAMP MOP OR AUTOSCRUB** using a quality CSI cleaner following the label directions.
3. **BURNISH** the floor with an appropriate pad and high-speed floor machine (1000-2000+RPM) or spray buff the floor with an electric machine to remove black heel marks, scuffs and scrapes.

NOTE: To avoid frequent stripping or as the finish begins to show wear, machine clean the floor, rinse and apply two thin coats of Quick EZ Gloss Coat.

This product is not hazardous as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Prevention: Observe good industrial hygiene practices.

Response: Wash hands after handling.

Storage: Store away from incompatible materials.

Disposal: Dispose of waste and residues in accordance with local authority requirements.

CSI - We Build Opportunity