

# FRESCO SAND

163-017



**CATEGORY**  
Panel

**PROPERTIES**

**CONTENT**  
100% Post-Consumer Recycled Polyester

**BACKING**  
None

**ADDITIONAL FINISHING AVAILABLE  
(CHECK FOR PRICING)**  
Nano-TEX

**FINISH**  
None

**WIDTH**  
66"

**WEIGHT**  
10 oz./linear yard

**SHOWN RR**  
No

**DIR**  
Yes

**ROLL LENGTH**  
80 yards

**VISUAL REPEAT**  
None

**BREAKING STRENGTH**  
Warp 100 min./Fill 100 min.

**SEAM SLIPPAGE**  
Warp: N/A lbs. / Fill: N/A lbs.

**ABRASION RESISTANCE**  
N/A

**PILLING RESISTANCE**

**COLORFASTNESS TO CROCKING**  
Dry: Class 4 min/Wet: Class 4 mi

**COLORFASTNESS TO LIGHT**  
40 hours

**FLAMMABILITY**  
Passes Cal 117 Section E; ASTM E84 Class 1 or A (Unadhered)

## CLEANING

**WS: Water/Solvent Cleaner** - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

[Additional cleaning details at www.mayerfabrics.com](http://www.mayerfabrics.com)

