

QUATTRO CHALK

300-007



CATEGORY
Seating/Panel

PROPERTIES

CONTENT
100% Polyester

BACKING
Acrylic

ADDITIONAL FINISHING AVAILABLE
(CHECK FOR PRICING)
Nano-Tex, NanoGuard

FINISH
Stain Repellent

WIDTH
54"

WEIGHT
13.06 oz./linear yard

SHOWN RR
No

DIR
Yes

ROLL LENGTH
55 yards

VISUAL REPEAT
Non-Matching

BREAKING STRENGTH
Warp 377/Fill 116

SEAM SLIPPAGE
Warp: 65 lbs. / Fill: 91 lbs.

ABRASION RESISTANCE
Passes 237,000 Double Rubs (Wyzenbeek)
Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

PILLING RESISTANCE
Class 5

COLORFASTNESS TO CROCKING
Dry: Class 4 min/Wet: Class 4 mi

COLORFASTNESS TO LIGHT
40 hours

APPLICATION
Indoor

FLAMMABILITY
Passes Cal 117-2013; NFPA 260/UFAC Class 1; ASTM E84 Class 1 or A (Unadhered); IMO A.652(16) 8.2. May comply with Cal. Tech. Bul. 133 when combined with appropriate components.

CLEANING

S: Solvent Cleaner - Spot clean, using a mild water-free solvent or dry cleaning product. Clean only in a well-ventilated room and avoid any product containing carbon tetrachloride or other toxic materials. Pretest a small area before proceeding. Always rinse promptly with clean water.

[Additional cleaning details at www.mayerfabrics.com](http://www.mayerfabrics.com)



GREENGUARD
GOLD Certified