

ELEMENT COPPER

316-009



CATEGORY
Seating

PROPERTIES

CONTENT
85% Antimony Free Polyester, 15% Polyester

BACKING
None

**ADDITIONAL FINISHING AVAILABLE
(CHECK FOR PRICING)**
NanoGuard

FINISH
INCASE with Antimicrobial Silver Ion
Technology

WIDTH
54"

WEIGHT
13 oz./linear yard

SHOWN RR
No

DIR
Yes

ROLL LENGTH
60 yards

VISUAL REPEAT
Non-Matching

BREAKING STRENGTH
Warp 311/Fill 213

SEAM SLIPPAGE
Warp: 86 lbs. / Fill: 75 lbs.

ABRASION RESISTANCE
Passes 130,000 Double Rubs (Wyzenbeek)

Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

PILLING RESISTANCE
Class 5

COLORFASTNESS TO CROCKING
Dry: Class 4/Wet: Class 3.5

COLORFASTNESS TO LIGHT
60 hours

FLAMMABILITY
Passes Cal 117 Section E; NFPA 260/UFAC Class 1. May comply with Cal. Tech. Bul. 133 when combined with appropriate components.

CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

[Additional cleaning details at www.mayerfabrics.com](http://www.mayerfabrics.com)

**GREENGUARD
GOLD Certified**

© Mayer Fabrics 2019

Specifications are subject to change. Current specifications are available at mayerfabrics.com
Mayer Fabrics | 500 S. Kitley Ave, Indianapolis, IN 46219

TF. 800.428.4415
T. 317.267.2626
F. 317.267.2629