

CARESSA ADMIRAL

CA-014



CATEGORY
Seating

PROPERTIES

CONTENT
80% Vinyl Phthalate Free face, 20% Polyester backing

BACKING
100% Polyester

FINISH
Soil and Stain Resistant Top Coat with Ink Resistant Technology

WIDTH
54"

WEIGHT
29 oz./linear yard

SHOWN RR
No

DIR
No

ROLL LENGTH
30 yards

VISUAL REPEAT
None

BREAKING STRENGTH
Warp 115/Fill 102

SEAM SLIPPAGE
Warp: 53 lbs. / Fill: 50 lbs.

ABRASION RESISTANCE
Passes 650,000 Double Rubs (Wyzenbeek)

Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

PILLING RESISTANCE
Class

COLORFASTNESS TO CROCKING
Dry: Class 4 min/Wet: Class 4 mi

COLORFASTNESS TO LIGHT
1000 hours

FLAMMABILITY
Passes NFPA 260/UFAC Class 1; Cal 117-2013; ASTM E84 Class 1 or A (Unadhered) (Adhered); Boston Fire Dept. Code (BFD IX-1); FMVSS 302;; IMO A.652 (16) 8.2 & 8.3.; IMO FTP 2010 Code MSC.307(88), Part 8, 3.1 & 3.2; NY/NJ Port Authority

CLEANING

CFC: Coated Fabrics Cleaning - Please refer to cleaning information section on Mayer website for complete cleaning info.

BC: Bleach Cleanable - 1 part bleach, 9 parts water = 10% bleach, 90% water solution. Do not clean/disinfect fabric for longer than 10 minutes using the 10% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

[Additional cleaning details at www.mayerfabrics.com](http://www.mayerfabrics.com)

Resilience^{SR}
ENDURING PROTECTION

GREENGUARD
Certified

© Mayer Fabrics 2019

Specifications are subject to change. Current specifications are available at mayerfabrics.com
Mayer Fabrics | 500 S. Kitley Ave, Indianapolis, IN 46219

TF. 800.428.4415
T. 317.267.2626
F. 317.267.2629